



EN ISO 20345:2011



RESOLUTE  
**SLANCIO BOA®**  
43458-02L

**S1P SRC**

**Size:** 36-48  
**Weight:** 580 gr.

**Fit:** 11

**Working Environment:**  
Multipurpose, Logistics and Light Industry, Components and Automotive, ESD Areas



**FEATURES**

**UPPER**

MicroFiber Suede  
SpiderMesh HT

**LINING**

3D Green Air 320 gr.

**ANTISLIP LINING**

DUALMICRO

**INSOLE**

Qrs01

**TOE CAP**

Fiber cap SXT

**RESISTANCE TO PERFORATION**

Textile resistant to 3.0 mm nail - X  
Method

**TYPE**

Low Shoe

**SOLE**

**PU / PU ESD-PLUS SRC**

Double density PU sole, Outer- and in-between sole with ESD compound. For use in contact with sensitive electronic equipment. Light and comfortable, very versatile, highly non-slip SRC Antislip standard.

**TECHNOLOGIES**

**Removable Insole**



Anatomical breathable insole. Resistant fabric with recycled open-cell foam that absorbs shocks and reduces fatigue. Eliminates sweat with its high ability to evaporate it. Continuous comfort for months and months of use

**Protection elements**



Composite toecap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable

**Lateral stability**



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

**Torsional stability**



Support made of rigid plastic material. It supports the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



**SRC (SRA+SRB)**

		RESOLUTE PU - PU
SRA CERAMIC DETERGENT SOLUTION	FLAT ≥0.32	0.39
	HEEL (CONTACT ANGLE °) ≥0.28	0.40
SRB STEEL GLYCEROL	FLAT ≥0.18	0.24
	HEEL (CONTACT ANGLE °) ≥0.13	0.23

EN ISO 20345:2011

**Electrical features**



Footwear suitable for "EPA" protected areas. IEC EN 61340-5-1:2016 IEC EN 61340-4-3:2018

**Other**



Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.